The Cleaning Resource

SAFETY DATA SHEET

1. Identification

Product identifier HIL-TEX+

Other means of identification

Recommended restrictions

SDS number 556N-22G Product code HIL00344 Wood Floor Seal Recommended use

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company name HILLYARD INDUSTRIES **Address** 302 North Fourth St.

St. Joseph, MO 64501

None known.

Contact person Regulatory Affairs

(816) 233-1321 (Ext. 8285) Telephone number

(816) 383-8485 Fax

regulatoryaffairs@hillyard.com E-mail

(800) 424-9300 Emergency telephone #

(Only in the event of chemical emergency involving a spill, leak, fire, exposure,

or accident involving chemicals.)

2. Hazard(s) identification

Not classified. Physical hazards **Health hazards** Not classified. Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements

None. **Hazard symbol** None. Signal word

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Wash hands after handling. Response

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-(2-ethoxyethoxy)ethanol		111-90-0	1 - < 3
Other components below reportable		90 - 100	

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Material name: HIL-TEX+ SDS US

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses.

Continue rinsing.

Ingestion Drink water as a precaution. Get medical attention if any discomfort continues.

Most important

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Material can be slippery when wet. Follow precautions for safe handling described in this safety data sheet. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. AIHA Workplace Environment	' _ '		
Components	Туре	Value	
2-(2-ethoxyethoxy)ethanol (CAS 111-90-0)	TWA	140 mg/m3	
•		25 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Material name: HIL-TEX+ SDS US 2/6

Individual protection measures, such as personal protective equipment

Where splashing of concentrate is a concern, use protective glasses with side shield. Eye/face protection

Skin protection

Hand protection Not normally needed. Other Not normally needed.

Respiratory protection No personal respiratory protective equipment normally required.

Thermal hazards None known.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

White opaque liquid **Appearance**

Physical state Liquid. Liquid. **Form** Color Milky white Odor Polymer odor **Odor threshold** Not available 7.5 - 8.5Ha

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling

range

> 200 °F (> 93.33 °C)

Flash point > 200.0 °F (> 93.3 °C) **Evaporation rate** < 1 Ethyl ether = 1 Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure 17.5 mm Hg Vapor density 0.7 AIR=1

Relative density Solubility(ies)

100 % Complete Solubility (water) Partition coefficient Not available

(n-octanol/water)

Not available **Auto-ignition temperature Decomposition temperature** Not available Not available **Viscosity**

Other information

8.50 lb/gal Density Percent volatile 83 - 85 %

VOC (Weight %) 0.42 % CARB VOC 2.42 % US EPA

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

1.02

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition No hazardous decomposition products are known.

products

Material name: HIL-TEX+ SDS US 3/6 HIL00344 Version #: 01 Issue date: 11-25-2014

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May be irritating to the skin.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

0---

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

T--4 D-----

Information on toxicological effects

Acute toxicity

D. 4

Product	Species	Test Results
HIL-TEX+		
Acute		
Dermal		
LD50	Rabbit	13596.1934 ml/kg estimated
		2261.9048 g/kg estimated
Inhalation		
LC50	Mouse	20475.5039 mg/l, 10 Minutes estimated
		9682.9971 mg/l, 1 Hours estimated
		9538.9053 mg/l, 2 Hours estimated
	Rabbit	20317.002 mg/l, 1 Hours estimated
	Rat	21902.0176 mg/l, 2 Hours estimated
		14697.4063 mg/l, 1 Hours estimated
Oral		
LD50	Guinea pig	11964.6494 g/kg estimated
	Mouse	371.7514 g/kg estimated
	Rat	74133.2344 mg/kg estimated
		10061.1826 ml/kg estimated
Components	Species	Test Results
2-(2-ethoxyethoxy)ethanol	(CAS 111-90-0)	
Acute		
Dermal		
LD50	Rabbit	8476 mg/kg
	Rat	6000 mg/kg
Oral		
LD50	Mouse	6.58 g/kg
	Rat	1920 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Material name: HIL-TEX+ SDS US

HIL00344 Version #: 01 Issue date: 11-25-2014

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species		Species	Test Results	
HIL-TEX+				
Aquatic				
Crustacea	EC50	Daphnia	31124.9453 mg/l, 48 hours estimated	
Fish	LC50	Fish	1433.7987 mg/l, 96 hours estimated	
Components		Species	Test Results	
2-(2-ethoxyethoxy)eth	anol (CAS 111-90-	0)		
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-(2-ethoxyethoxy)ethanol -0.54

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List or Exempt.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Material name: HIL-TEX+

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region Inventory name

On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-25-2014

Version # 01

HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Material name: HIL-TEX+ SDS US